


PRODUCT DATASHEET

DR DS-P- 32/220-240/750 PL FLEX 625

PANEL FLEX DRIVER | Constant current



Areas of application

- Suitable for PANEL FLEX 30 W / 32 W

Product benefits

- High flexibility due to adjustable output currents with a switch on the driver
- Low flickering enables high light quality as well as good visual comfort
- High efficiency and reliability
- 7 years guarantee

Product features

- Available in 30 W, 32 W
- Protection class: II
- Type of protection: IP20
- Supply voltage: 220...240 V
- Operating frequency: 0/50/60 Hz
- Suitable for central battery emergency installations acc. to EN 60598-2-22


TECHNICAL DATA

Electrical data

Nominal wattage	32.00 W
Nominal voltage	220...240 V
Mains frequency	0/50/60 Hz
Nominal current	700 mA
Inrush current	11.1 A
Power factor λ	> 0.90
Total harmonic distortion	< 15 %
Protection class	II
Dimming interface	Not dimmable

Dimensions & Weight

Length	125.00 mm
Width	60.00 mm
Height	30.00 mm
Product weight	105.00 g



DR DS-P PL FLEX

Materials & Colors

Body material	Plastic
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-10...+50 °C
Temperature range at storage	-20...+80 °C
Type of protection	IP20
Dimmable	No

Control gear

Nominal output current	750 mA
ECG lifetime	100000 h

Emergency lighting

Type of Emergency Lighting (EL)	EL certified driver (0Hz / DC operation) for central battery operation included
---------------------------------	---

Certificates & Standards

Standards	CE / CB / ENEC / UKCA / EAC / EPD / EL
-----------	--

Additional product data

Product remark	Available from June 2024
----------------	--------------------------

DOWNLOAD DATA

Documents and certificates		Document name
	User instruction / safety instructions	DR DS-P PL FLEX
	Legal information	DR DS-SENS- SF FL
	Legal information	Informationstext 18 Abs 4 ElektroG
	Declarations of conformity	Driver PL FLEX
Tender texts		Document name
	Tender documents	PANEL FLEX DRIVER 32 220 240 750 PL FLEX 625-en

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075843691	Folding box 1	82 mm x 34 mm x 182 mm	154.00 g	0.51 dm ³
4058075843837	Shipping box 20	427 mm x 157 mm x 217 mm	3438.00 g	14.55 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.