

PRODUCT DATASHEET

ULTRA COMMERCIAL DOWNLIGHT 12W

195MM TRI DIM

ULTRA COMMERCIAL DOWNLIGHT | The Ultra Commercial Downlight offers an economical solution for both new projects and the replacement of larger diameter luminaires, such as older compact fluorescent



Areas of application

- Public areas
- Reception areas and foyers
- Entrances / Hallways
- Retail and small shops
- Hospitality
- Commercial applications
- Lobbies

Product benefits

- Phase dim: 10.5W, 12W, 14W, 19/14W, 20/14W, 30/23W, 40/30W
- DALI: 11W, 14.5W, 18W, 18/15W, 20/16W, 29/23W, 39/29W
- Cut out size in 92mm, 118mm, 135mm, 160mm, 195mm, 240mm
- Available in phase dimming and DALI

Product features

- TRI colour in 3000K, 4000K and 5700K
- Type of protection: IP54
- Pre-wired with 1.6m flex and plug
- Lifetime up to 50,000 h
- High luminous efficacy: up to 135 lm/W

TECHNICAL DATA

Electrical data

Nominal wattage	12.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Power factor λ	> 0.90
Protection class	II
Operating mode	External LED driver

Photometrical data

Luminous flux	1450 lm / 1600 lm / 1550 lm
Luminous efficacy	135 lm/W
Color temperature	3000 K / 4000 K / 5700 K
Light color (designation)	Warm White / Cool White / Cool Daylight
Color rendering index Ra	80
Beam angle	105 °
UGR	< 22

Dimensions & Weight

Diameter	230.00 mm
Height	63.00 mm
Product weight	475.00 g

LDECO DL 195MM TRI

Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP54/IP20
Dimmable	Yes
Type of dimming	PHASE CUT

Mounting type	Recessed
Mounting location	Ceiling
Application environment	Indoor
Mounting diameter	195 mm
Replaceable light source	No

Lifespan

Lifespan L70/B50 at 25 °C	50000 h ¹⁾
---------------------------	-----------------------

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

Replaceable light source (EPREL)	Not replaceable
----------------------------------	-----------------

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4099854333859	Folding box 1	290 mm x 266 mm x 106 mm	643.00 g	8.18 dm ³
4099854333866	Shipping box 8	547 mm x 304 mm x 474 mm	6131.00 g	78.82 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.