

## PRODUCT DATASHEET

### HAL CL A 57 W 240 V B22d

HALOGEN CLASSIC A | Halogen lamps, classic bulb shape



---

#### Areas of application

- General illumination
- Mood lighting
- Entrance lighting
- Restaurants, hotels and similar prestigious applications

---

#### Product benefits

- Simple direct replacement for conventional incandescent lamps
- The same pleasant quality of light as that of an incandescent lamp
- Instant 100 % light, no warm-up time
- Contains no mercury
- UV filter

---

#### Product features

- 100 % dimmable
- Perfect color rendering ( $R_a: 100$ )
- Average life: 2,000 h

TECHNICAL DATA

Electrical data

|                      |         |
|----------------------|---------|
| Nominal wattage      | 57 W    |
| Construction wattage | 57.00 W |
| Nominal voltage      | 240 V   |

Photometrical data

|                          |         |
|--------------------------|---------|
| Luminous flux            | 915 lm  |
| Luminous efficacy        | 16 lm/W |
| Color temperature        | 2800 K  |
| Color rendering index Ra | 100     |
| Light color              | 1028    |

Light technical data

|               |     |
|---------------|-----|
| Starting time | 0 s |
|---------------|-----|

Dimensions & Weight

|                           |          |
|---------------------------|----------|
| Overall length            | 96.00 mm |
| Light center length (LCL) | 73,0 mm  |
| Diameter                  | 55.00 mm |
| Product weight            | 31.00 g  |

Additional product data

|                             |      |
|-----------------------------|------|
| Base (standard designation) | B22d |
| Mercury-free                | Yes  |
| Design / version            | Bulb |

Capabilities

|                  |     |
|------------------|-----|
| Burning position | Any |
|------------------|-----|

Country-specific categorizations

|                 |                          |
|-----------------|--------------------------|
| ILCOS           | HSGSAF/UB-57-240-B22D-73 |
| Order reference | 64544 ACLAFR 57          |

Energy labelling regulation data acc EU 2019/2015

|                                                     |          |
|-----------------------------------------------------|----------|
| Light source cap-type (or other electric interface) | B22d     |
| Length                                              | 93.00 mm |
| Height                                              | 55.00 mm |
| Width                                               | 55.00 mm |

### Safety advice

- Do not touch the lamp if broken.
- Must not be used if outer bulb is defective.
- Lamp to be used only in a closed luminaire.

### DOWNLOAD DATA

| Documents and certificates                                                       |                                        | Document name               |
|----------------------------------------------------------------------------------|----------------------------------------|-----------------------------|
|  | User instruction / safety instructions | 334575_Mounting Instruction |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321629531 | Folding box<br>1             | 55 mm x 55 mm x 97 mm                | 40.00 g      | 0.29 dm <sup>3</sup> |
| 4008321845238 | Shipping box<br>20           | 286 mm x 234 mm x 105 mm             | 895.00 g     | 7.03 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.